



NEW REFRIGERATED MODEL
enoline elite 2.5

NEW REFRIGERATION
LOW NOISE EMISSION
HIGH PERFORMANCE

NEW GENERATION WINE SERVING SYSTEM

enoline elite 2.5

- Available model:
enoline 4+4 bott. Refrigerated (8 bottles in a row)
The system has a dual temperature compartment managed separately from 6 to 18 °C (from 43 to 64 °F) in order to serve both red and white wines.
It is also possible to move the internal divider to offer a 5+3 configuration.
- **Temperature setting:** from 6 to 18 °C (from 43 to 64 °F).
- **Cooling system:** by refrigerator compressor.
- **Use and system activation:** the system can be used either behind the counter (without wine card) or self-service (with wine card).
- **Gas supply:** food grade Nitrogen or Argon (cylinder or generator not included).
- **Volumes:** 1 or 3 configurable volumes with touch screen key display.
- **Display:** each position has an LCD graphic touch screen interactive display to monitor the dispenser's functions. A central LCD graphic screen supplies general information.
- **Materials:** stainless steel, prepainted steel, glass.
- **Colors and finishings:** In addition to the classic stainless steel finish, it is possible to choose from the following

colors: "black elegance, "black elegance precious" (pistons, handles and spouts in gold finish) or RAL customised colours (www.ralcolor.com).

- **Lighting:** double LED. Light intensity can be set; it changes according to different functions.
- **Environment control:** a junction box performs a check on all external environment conditions (temperature, pressure, humidity) in order to auto-adjust the dispenser's efficiency.
This guarantees increased precision of pour volumes and better functionality of the refrigeration system.
- **Nitrogen/Argon leak control:** a designated pressure control system highlights any gas leak directly on the display.
- **Bottles lifting system:** by pneumatic pistons.
- **Positioning:** can be lined up on both sides; support furniture needed.
- **Wine card types:** chip card (SMART card) and RFID MIFARE (shared-use MAD system compatible). Finger print, magnetic stripe or bar code customizable upon request.
- **Modules interfacing:** LAN network, TCP/IP protocol.

| model | L | H | D | weight | electrical requirements |
|-------------------|---------|-------|---------|--------|---------------------------|
| enoline 2.5 4+4 R | 97,1 cm | 67 cm | 35,4 cm | 72 kg | 100 V 50-60 Hz 135 W |
| enoline 2.5 4+4 R | 97,1 cm | 67 cm | 35,4 cm | 72 kg | 115 V 60 Hz 135 W |
| enoline 2.5 4+4 R | 97,1 cm | 67 cm | 35,4 cm | 72 kg | 110-127 V 60 Hz 135 W |
| enoline 2.5 4+4 R | 97,1 cm | 67 cm | 35,4 cm | 72 kg | 220-240 V 50 Hz 135 W |